



# coatmaster

measure up. contactless.

coatmaster Atline

## Noncontact coating thickness measurement in laboratory and production.



PATENTED  
TECHNOLOGY



### **Avoid rework and rejects.**

Detect and correct deviations early in the process.



### **For complex shaped parts.**

Also on curved surfaces, on inner sides and corners and edges.



### **Mobile measuring station.**

Can be used for several coating lines.

# Technical Data

Wet paints before drying	1 – 2000 $\mu\text{m}$
Powder coatings before curing	1 – 2000 $\mu\text{m}$
Cured powder / dried paints	1 – 2000 $\mu\text{m}$
Measuring time <sup>1</sup>	from 20 ms
Distance tolerance <sup>1</sup>	5– 120 cm
Tilt tolerance <sup>1</sup>	$\pm 70^\circ$
Measurement on moving parts <sup>1</sup>	120 m/min
Relative standard deviation <sup>2</sup>	< 1 %
Measures coatings of any color (incl. white)	yes
Real-time data access via ERP and browser	yes

<sup>1</sup> Depending on coating and substrate material

<sup>2</sup> 60  $\mu\text{m}$  powder coating before curing (all colors incl. white) on aluminium, 5 cm working distance



## coatmaster AG

Flugplatzstrasse 5  
CH-8404 Winterthur  
Tel +41 52 212 02 77  
info@coatmaster.com

[www.coatmaster.com](http://www.coatmaster.com)



## Learn more

All information about thickness measurement with coatmaster

[www.coatmaster.com/references](http://www.coatmaster.com/references)